



TECHNICAL SPECT

CRAFT PLAS

Code F2050

Acrylic emulsion based, matt final coat decorative interior paint.

APPLICATION

Craft Plas is applied on properly prepared interior mineral surfaces like rough cast, concrete, cement sheet, plaster panel and old painted surfaces with suitable undercoating.

FEATURES

- Resistant to wiping, and easily cleaned.
- Thanks to its high vapour permeability, it enables the vapour to be thrown out and lets the surface breathe.
- Strong covering.
- Water-based, odor-free; harmless to human health and environment.

SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with FIRACOLOR ACRYLIC PUTTY THIN.

APPLICATION INSTRUCTIONS*

- Surfaces with old paint or surfaces that will be painted must be undercoated with FIRACOLOR UNIFIRA.
- CRAFT PLAS must be mixed well prior to application.
- Prior to application, CRAFT PLAS must be diluted with 20% fresh water maximum and applied in 2 coats with roll, brush or spraying method. Minimum 5 hours wait time must be placed between coats.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

DRYING TIME: The contact time is 5-6 hours, and thorough-dry time is 24 hours in environment of 23°C.

PACKING: 2,5 L – 7,5 L – 15 L

CONSUMPTION: Depending on surface smoothness and application methods, for single coat application: 11-14 m²/lt or 0,070 – 0,085 L /m²

FLASH POINT: Water-based, non-flammable

STORAGE: Store in enclosed packaging for 1 year between +5°C to +30°C

WARNINGS: Keep away from places where children can reach. Avoid eye and skin contact.

*For a healthier application, the technical sheet of the product must be reviewed.

"Firacolor is a brand of Ayfira Inc."