

TECHNICAL SPECT

CRATERA

Code: F0130

Mineral-based and natural decorative plaster with high vapor level and air permeability that provides to obtain a travertine view on the surface of the internal walls.

APPLICATION

On all the interior walls, plaster, gross concrete and timber surfaces; it is used together with its appropriate primer after the surface preparation.

FEATURES

- It is such a material that provides to create effects with different patterns during application by the skills of the master / implementer.
- Via its high water vapor permeability; it provides the vapor to be discharged and the surface to breath.
- Water-based, odor-free; harmless to human health and environment.
- It provides a pleasant odor for the application environments via its perfume property.

SURFACE PREPARATION

 After removing all kinds of dirt, grease, bloated paint and dust from the surfaces where Crater will be applied, the surface defects should be corrected by FİRACOLOR ACRYLIC PUTTY and undercoated with FİRAPRİMER.

APPLICATION INSTRUCTIONS*

- Applied by a stainless steel trowel without reducing.
- The primer coat application should be at least 1 mm thick.
- When dried; pressure is applied to the product in order to obtain a smooth surface and then the finishing coat is applied. In order to obtain a shiny finish, pressure is applied by a dry steel trowel before the surface dries.
- The environment of application must be kept above +5 °C within 24 hours during and after the application.

DRYING TIME: The contact time is 5-6 hours thorough-dry time is 48 hours in environment of 23oC.

PACKING: 10 kg - 20 kg

CONSUMPTION: For two layers of application according to the surface smoothness and application techniques, 0.9-1 kg/m².

FLASH POINT: Water-based, non-flammable

STORAGE: Store in enclosed packaging for 1 year between +5°C to +30°C

WARNINGS: Keep out of the reach of children. Avoid contact with eyes and skin.

For a healthier application, the technical bulletin of the product must be examined.

"Firacolor is a brand of Ayfira Inc."