



TECHNICAL SPECT

ECO ACRYLIC

Code F3040

Acrylic emulsion based, long life, matt, final coat decorative exterior paint.

APPLICATION

Eco Acrylic is used on external sides on plaster, exposed concrete, cement sheet and eternit with suitable undercoating.

FEATURES

- Resistant to wiping, and easily cleaned.
- Easy application, high covering.
- Resistant against weather conditions like rain, snow, extreme hot or cold and abrasion.
- Gives a modern and clean look to surfaces with decorative non-fading colours.
- Highly vapour permeable, enables the vapour to be thrown out and lets the surface breathe.
- Water based and odour-free; doesn't harm human health and environment

SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with FIRACOLOR ACRYLIC PUTTY THICK.
- Previously painted surfaces, or surfaces that will be painted must be undercoated with FIRACOLOR UNIFIRA. We recommend using the same colour of undercoat as the selected siding colour.

APPLICATION INSTRUCTIONS*

- Mix ECO ACRYLIC well prior to application.
- Prior to application, dilute ECO ACRYLIC 15-20% fresh water, and apply in 2 coats with roller, brush or spraying method. Wait for 4 hours minimum between coats.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

DRYING TIME: The contact time is 4-5 hours, and thorough-dry time is 24 hours in environment of 23°C.

PACKING: 15 L

CONSUMPTION: Depending on surface smoothness and application methods, for single coat application: 12-14 m²/lt or 0,070 – 0,080 L /m²

FLASH POINT: Water-based, non-flammable

STORAGE: Store in enclosed packaging for 1 year between +5°C to +30°C

WARNINGS: Keep away from places where children can reach. Avoid eye and skin contact.

*For a healthier application, the technical sheet of the product must be reviewed.



TECHNICAL SPECT

"Firacolor is a brand of Ayfira Inc."