



TECHNICAL SPECT

FIRA GLOSS

Code F2010

Acrylic emulsion based, bright, long life, decorative final coat interior paint.

APPLICATION

Fira Gloss is applied on interior and exterior faces to old painted or mineral surfaces like new rough plaster, concrete, cement sheet, gypsum panel, wooden and metal surfaces with suitable undercoat.

FEATURES

- Doesn't lose brightness in time, does not etiolate.
- Wide range of applications. Can be applied to all kinds of surfaces interior and exterior; wood, metal and mineral and adheres perfectly to every surface.
- Easy to apply.
- Not affected by heavy weather conditions like rain, snow, humidity hot or cold. Doesn't blister or crack.
- Throws out the humidity forming inside, and allows the buildings to breathe.
- Perfectly wipeable.
- Water-based, odor-free; harmless to human health and environment.

SURFACE PREPARATION

- Clean application surface of all dirt, oil, dust that will decrease adherence, completely clean old and blistered paint to provide a dry, clean and strong surface.

APPLICATION INSTRUCTIONS*

- Before applying on new mineral surfaces, wait for 28 days minimum for the surface to cure.
- Finely sandpaper old synthetic based surface, and remove sandpaper dust from the surface.
- If necessary, level the application surfaces with FIRACOLOR ACRYLIC PUTTY Thin.
- After applying an undercoat suitable to the surface structure, dilute FIRA GLOSS with 5-10% fresh water and apply in 2 coats with finely saturated hair brush, moher roll or spraying method. Wait a minimum of 5 hours between coats.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

DRYING TIME: The contact time is 5-6 hours, and thorough-dry time is 24 hours in environment of 23°C.

PACKING: 2,5 L – 7,5 L – 15 L

CONSUMPTION: Depending on surface smoothness and application methods, for single coat application: 13-15 m²/lt or 0.065 -0.075 L /m²

FLASH POINT: Water based, non-flammable.

STORAGE: Store in enclosed packaging for 1 year between +5°C to +30°C

WARNINGS: Keep away from places where children can reach. Avoid eye and skin contact.

*For a healthier application, the technical sheet of the product must be reviewed

"Firacolor is a brand of Ayfira Inc."