



## TECHNICAL SPECT

### FIRALUX

Code F3020

Acrylic emulsion based, long life, matt, final coat decorative exterior paint.

#### APPLICATION

Firalux is used on external sides on plaster, exposed concrete, cement sheet and eternit with suitable undercoating.

#### FEATURES

- Resistant to wiping, and easily cleaned.
- Resistant against weather conditions like rain, snow, extreme hot or cold and abrasion.
- Gives a modern and clean look to surfaces with decorative non-fading colors.
- Highly vapour permeable, enables the vapour to be thrown out and lets the surface breathe.
- Easy application, high covering.
- Water-based, odor-free; harmless to human health and environment

#### SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with FIRACOLOR ACRYLIC PUTTY THICK.
- Previously painted surfaces, or surfaces that will be painted must be undercoated with FIRACOLOR UNIFIRA. We recommend using the same color of undercoat as the selected siding color.

#### APPLICATION INSTRUCTIONS\*

- Mix FIRALUX well prior to application.
- Prior to application, dilute FIRALUX with 15-20% fresh water, and apply in 2 coats with roller, brush or spraying method. Wait a minimum of 4 hours between coats.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

**DRYING TIME:** The contact time is 4-5 hours, and thorough-dry time is 24 hours in environment of 23°C.

**PACKING:** 2,5 L – 7,5 L - 15 L

**CONSUMPTION:** Depending on surface smoothness and application methods, for single coat application: 12-14 m<sup>2</sup>/lt or 0,070 – 0,080 L /m<sup>2</sup>

**FLASH POINT:** Water-based, non-flammable

**STORAGE:** Store in enclosed packaging for 1 year between +5°C to +30°C

**WARNINGS:** Keep away from places where children can reach. Avoid eye and skin contact.

\*For a healthier application, the technical sheet of the product must be reviewed.

"Firacolor is a brand of Ayfira Inc."