



TECHNICAL SPECT

GLAZED Code F2020

Acrylic emulsion based, silicone added, super covering interior paint in semi-bright texture.

APPLICATION

Glazed is applied on properly prepared interior mineral surfaces like rough cast, concrete, cement sheet, plaster panel and old painted surfaces with suitable undercoating.

FEATURES

- Easily cleaned with perfect wipeability, does not stain.
- Provides a semi-bright texture to the application surface.
- Highly vapour permeable, enables the vapour to be thrown out and lets the surface breathe.
- Highly covering.
- Water-based, odor-free; harmless to human health and environment.

SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with FIRACOLOR ACRYLIC PUTTY THIN.

APPLICATION INSTRUCTIONS*

- Undercoat previously painted or very dirty surfaces FIRACOLOR UNIFIRA.
- Mix GLAZED well prior to application.
- Prior to application, dilute GLAZED with 5-10% fresh water, and apply in 2 coats with roller, brush or spraying method. Wait a minimum of 5 hours between coats.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

DRYING TIME: The contact time is 5-6 hours, and thorough-dry time is 24 hours in environment of 23°C.

PACKING: 2,5 L – 7,5 L-15 L

CONSUMPTION: Depending on surface smoothness and application methods, for single coat application: 13-15 m²/lt or 0.065 -0.075 L /m²

FLASH POINT: Water-based, non-flammable

STORAGE: Store in enclosed packaging for 1 year between +5°C to +30°C

WARNINGS: Keep away from places where children can reach. Avoid eye and skin contact.

*For a healthier application, the technical sheet of the product must be reviewed.

"Firacolor is a brand of Ayfira Inc."