



## TECHNICAL SPECT

### NATURIN NATURAL

Code F3110– F3111

Acrylic emulsion based, ready to use decorative plaster containing natural colour stones.

#### APPLICATION

NATURIN NATURAL is used in exterior faces of all kinds of buildings on rough plaster, exposed concrete, cement sheet and insulation systems as final coat material, along with suitable undercoat.

#### FEATURES

- Manufactured in two different sizes; 1 mm and 3mm.
- Vapour permeable, enables the vapour to be thrown out and lets the surface breathe.
- Covers up the faults on the surface with the thick layer of film that forms during application.
- Not affected from external factors, and weather conditions like rain, snow, humidity, extreme hot or cold and its colours do not fade.
- Resistant to UV and alkaline.
- Water-based, odor-free; harmless to human health and environment

#### SURFACE PREPARATION

Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with FIRACOLOR ACRYLIC PUTTY.

#### APPLICATION INSTRUCTIONS\*

- Previously painted surfaces, or surfaces that will be painted must be undercoated with FIRACOLOR UNIFIRA.
- Mix NATURIN NATURAL mineral plaster well until it achieves a homogenous consistency.
- Spread NATURIN NATURAL mineral plaster on the entire surface with equal thickness with steel spud.
- Finish NATURIN NATURAL mineral plaster with steel spud 20 minutes after it is spread on the surface under normal weather conditions.
- Clean the spud used for finishing with water from time to time.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

**DRYING TIME:**The contact time is 4-6 hours, and thorough-dry time is 24 hours in environment of 23°C.

**PACKING:** 25 kg

**CONSUMPTION:** Depending on surface smoothness and application methods, for single coat application:

1 mm = 2.2 -2.5 kg/m<sup>2</sup>

3 mm = 3 -3.8 kg/m<sup>2</sup>

**FLASH POINT:** Water-based, non-flammable

**STORAGE:** Store in enclosed packaging for 1 year between +5°C to +30°C

**WARNINGS:** Keep away from places where children can reach. Avoid eye and skin contact.

\*For a healthier application, the technical sheet of the product must be reviewed.

"Firacolor is a brand of Ayfira Inc."