



TECHNICAL SPECT

PUREPLAS

Code F2030

Acrylic emulsion based, silky matt texture decorative interior paint.

APPLICATION

PUREPLAS is applied on properly prepared interior mineral surfaces like rough cast, concrete, cement sheet, plaster panel and old painted surfaces with suitable undercoating.

FEATURES

- Easily cleaned with perfect wipeability, does not stain.
- Silky matt texture gives a silky matt brightness to the wall.
- Highly vapor permeable, enables the vapor to be thrown out and lets the surface breathe. Highly covering.
- Water-based, odor-free; harmless to human health and environment.

SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with FIRACOLOR ACRYLIC PUTTY THIN.

APPLICATION INSTRUCTIONS*

- Previously painted or very dirty surfaces must be undercoated with FIRACOLOR UNIFIRA.
- Mix PUREPLAS well prior to application.
- Prior to application, dilute PUREPLAS with 5-10% fresh water, and apply in 2 coats with roller, brush or spraying method. Wait a minimum of 5 hours between coats.
- The environment of application must be kept above +5 ° C within 24 hours during and after the application.

DRYING TIME: The contact time is 5-6 hours, and thorough-dry time is 24 hours in environment of 23°C.

PACKING: 2,5 L – 7,5 L – 15 L

CONSUMPTION: Depending on surface smoothness and application methods, for single coat application: 13-15 m²/lt or 0.065 -0.075 L /m²

FLASH POINT: Water-based, non-flammable

STORAGE: Store in enclosed packaging for 1 year between +5°C to +30°C

WARNINGS: Keep away from places where children can reach. Avoid eye and skin contact.

*For a healthier application, the technical sheet of the product must be reviewed.

"FiraColor is a brand of Ayfira Inc."